



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

UNI THINNER SLOW

Article number: 13235 (1L), 13238 (5L)

Intended use: Car refinishing Product/ Thinner, Diluent

General characteristics: Effective organic solvent mix of slow evaporation

for the dilution of 2K Ground coats, 2K Top coats and 2K Clearcoats. For further information concernig typical or optimum levels of use and for more precise details, please consult our Product Informations for the base products

Physical and Chemical Characteristics:

Colour shade	colourless					
Mixing ratio						
Hardener						
Thinners						
Spraying viscosity 20° C						
Application	spraying pressure		spraying nozzle		spraying operations	
Air / Flowjar – Spray gun						
Airless / Airmix						
Pot life						
Coat thickness / dry film						
Curing time / Flash off time				_		
Dry	recoat time	du	st dry	set	to touch	full hardness
Object Temp. 20° C Object Temp. 60° C						

Safety instructions:

Keep containers tightly closed. Keep away from heatand flame, fire heat or other potential sources of ignition. The preparation may charge electrostatically. Always use earthing leads when taking out or transfering from one container to another.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.