



## ***TECHNICAL DATA SHEET***

### **CHAMÄLEON HEAT RESISTANT SPRAY**

<b>Article number:</b>	<b>26601 (Black), 26602 (Silver),</b>
<b>Intended use:</b>	Car refinishing Product/ Preparation
<b>General characteristics:</b>	High quality lacquer to treat surfaces, treated and untreated, which are exposed to very high temperatures.

#### **Product characteristics:**

- Heat resistant
- Excellent adhesion
- Resistant to petrol, chemicals and weather influences

#### **Physical and Chemical**

Contents  
Base  
VOC-content  
Solid content  
Gloss  
Coverage  
Dust dry Tack  
free Hardened  
Heat resistant

#### **Characteristics**

400 ml  
Silicone resin  
Approximately 84% w/w  
Approximately 16% w/w  
Satin matt  
1,25 to 1,75 m<sup>2</sup>  
After 5 to 10 minutes  
After 10 to 15 minutes  
After 30 to 60 minutes (160°C)  
To 800°C

#### **Usage:**

Before use, carefully read the directions on the packaging and act accordingly.  
Chamäleon GmbH – Technical Data Sheet

### **Pre Treatment:**

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Do not apply any primer.

### **Treatment:**

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the heat resistant lacquer in several thin layers. Before applying the next layer, again shake the aerosol. Allow to dry at room temperature for one hour. Then, heat for 30 to 60 minutes (160°C) in order to harden the paint layer. Smoke develops during the lacquer hardening process.

### **After use:**

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:  
[info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.