



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

CHAMÄLEON BITUM BRUSHABLE

Article number: **37101**

General characteristics:

A unique blend of raw materials and special processing results in a product that has adhesion most common surfaces and gives excellent protection. The product should be used at temperatures between 15 °C and 35 °C. Bitum brushable gives excellent and durable protection against rust and stone chip and has sound deadening properties.

Application:

As Corrosion protective coating on metal surfaces, especially for application on cars such as the under side of floor panels, the inside of wheel arches on parts of the chassis, subframes, ect.. Do not apply on parts of the braking system or on part of the exhaust system. RC 112 can be applied on bare metal but for extra protection the use of an anti corrosion primer is advised.

Properties:

Extreme good barrier formation, Easy application, excellent anti sagging properties. Resistant to water, brine, acids and alkaline. Compatible with original PVC under coatings. Can only be over sprayed/painted with bitumen product (not over paintable)

