

## GENERAL INFORMATION

1-060 2K Structure Coat Fine is an additive to create a structured surface in combination with HS420, HS and MS top coats. This additive has been developed for commercial vehicles, passenger cars and industrial coatings.

### MIXING RATIO



2 : 1 Top coat : Structure Coat

### GUN SET UP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

### APPLICATION



See TDS HS420, HS and MS Clear Coats and Top Coats.

### FLASH OFF AND DRY TIMES



See TDS HS420, HS and MS Clear Coats and Top Coats.



### SUBSTRATES



See TDS HS420, HS and MS Clear Coats and Top Coats.

### POT LIFE AT 20°C / 68°F



See TDS HS420, HS and MS Clear Coats and Top Coats.

### COMPONENTS



MM 2000 - 2099 BeroMix 2000 Series  
 MM 3000 - 3046 BeroThane HS420 3000 Series  
 All HS420 clear coats  
 All MS clear coats

**For compatibility see TDS Top Coats and Clear Coats.**

### ADDITIVES



-

### SURFACE PREPARATION



See TDS HS420, HS and MS Clear Coats and Top Coats.

**Mask entire vehicle to eliminate unwanted overspray.**



### NEXT LAYER



-

### PHYSICAL DATA

PHYSICAL DATA 1-060 2K STRUCTURE COAT FINE		
Chemical Base	Polyester resin with Polypropylene wax	
Physical Properties	Viscosity (RTS)	-
	Specific Gravity (kg/l)	1,022
	Flash Point Closed Cup	27°C / 80.6°F
	Volume % Solids	63.3
	Economy	-
	Gloss	-
	Colour	Milky



**DEBEER**  
REFINISH

**1-060**  
2K Structure Coat Fine

## PROTECTION

Use suitable respiratory protection (*fresh air supply respirator is strongly recommended*).



For more detailed information please visit the following link for the Safety Data Sheet:

[https://sds.de-beer.com/en/debeer/choose\\_localization](https://sds.de-beer.com/en/debeer/choose_localization)

## CLEAN UP



1-051 Gun Cleaner

## STORAGE/SHELF LIFE

Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).



## NOTES

-